



AB

Technical requirement:

- 1. Creepage distance: 2250mm
- 2. Cantilever strength: 6kN
- 3. Torsion strength: 2.5kN.m
- 4. Power frequency wet withstand: 140kV
- 5. Lightning impulse withstand voltage: 325kV
- 6. Color: Brown
- 7. Applicable standard: IEC 60273

5		FITTING	1	QT450-10			
4		PORCELAIN	1	IV			
3		CEMENT					
2		CORK	1				
1		FITTING	1	QT450-10			
No	DRAWING No	NAME	QTY	MATERIAL	ONE WEIGHT	TOTAL WEIGHT	NOTE
					DRAWING No	2878	
					PHASS SIGN	WEIGHT	SCALE
					TOTAL 2 PAGES	PAGE 1	
SIGN	QTY	REJIGGER No	NAME	DATE	<p style="font-size: 2em; text-align: center;">INSULATOR</p> <p style="text-align: center; font-weight: bold; font-size: 1.5em;">C6-325</p>		
DRAWN							
CHECKED							
APPROVE				MATERIAL			
DATE							
					<p style="font-weight: bold; font-size: 1.5em;">POLIPAR®</p> <p style="font-size: 0.8em;">THE POWER OF FUTURE</p>		